

HUMIDITY

Hygro-Thermo Transmitter compact

Part number: 1.1005.54.xxx

The data are output as electrical analogue signals. The transmitters consist of a capacitive humidity element and a Pt 100 resistance thermometer. For outdoor installation we recommend the use of the weather- and thermal radiation shield.

Order no.: 1.1025.55 xxx



Specification

Part number: 1.1005.54.xxx

Temperature	
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B
Rel. Humidity	
Measuring range	0 ... 100 % rel. h.
Accuracy	± 2% rel. h. (@ 5 ... 95 % rel. h. and 10 ... 40 °C)
Meas. element	Capacitive
General	
Electr. connection	5 m cable
Protection	IP 30 for sensors IP 65 for electronic
Dimension	Ø 20 x 124 (180) mm
Weight	0.45 kg

Versions

As per 1.1005.54.xxx, but:

Product number 1.1005.54.000

Temperature	
Measuring range	-30 ... +70 °C
Accuracy	±0,1 K (PT100)
Electr. output	PT100
Rel. Humidity	

Electr. output	0 ... 1 V
----------------	-----------

General

Power supply	6 ... 30 V DC
--------------	---------------

Product number 1.1005.54.160

Temperature

Measuring range	-30 ... +70 °C
-----------------	----------------

Accuracy	±0,2 K
----------	--------

Electr. output	0 ... 1 V
----------------	-----------

Rel. Humidity

Electr. output	0 ... 1 V
----------------	-----------

General

Power supply	6 ... 30 V DC
--------------	---------------

Product number 1.1005.54.161

Temperature

Measuring range	-30 ... +70 °C
-----------------	----------------

Accuracy	±0,2 K
----------	--------

Electr. output	0 ... 10 V
----------------	------------

Rel. Humidity

Electr. output	0 ... 10 V
----------------	------------

General

Power supply	15 ... 30 V DC
--------------	----------------

Product number 1.1005.54.173

Temperature

Measuring range	-30 ... +70 °C
-----------------	----------------

Accuracy	±0,2 K
----------	--------

Electr. output	0 ... 5 V
----------------	-----------

Rel. Humidity

Electr. output	0 ... 5 V
----------------	-----------

General

Power supply	10 ... 30 V DC
--------------	----------------

Product number 1.1005.54.241

Temperature

Measuring range	-30 ... +70 °C
-----------------	----------------

Accuracy	±0,3 K
----------	--------

Electr. output	4 ... 20 mA
----------------	-------------

Rel. Humidity

Electr. output	4 ... 20 mA
----------------	-------------

General

Power supply	12 ... 30 V DC
--------------	----------------

Product number 1.1005.54.441




Temperature

Measuring range	-40 ... +60 °C
Accuracy	±0,3 K
Electr. output	4 ... 20 mA
Rel. Humidity	
Electr. output	4 ... 20 mA
General	
Power supply	12 ... 30 V DC

Product number 1.1005.54.461

Temperature	
Measuring range	-40 ... +60 °C
Accuracy	±0,2 K
Electr. output	0 ... 10 V
Rel. Humidity	
Electr. output	0 ... 10 V
General	
Power supply	15 ... 30 V DC

Accessories

Product	Product name	Brief description
	Teflonfilter with gauze ZE 20 1.1005.54.901	This hood is placed over the sensor and protects the measurement element from coarse dirt.
	Sinter Filter ZE 21 1.1005.54.902	This basket is placed over the sensor and protects the measurement element from high wind speed (>5 m/s) and increased dust. A necessity for sensors in use in exposed areas, eg. in marine climates, desert, mountains.
	Wall Holder 1.1005.54.903	for mounting the temperature (2.1280.xx.xxx) or hygrothermo Sensor (1.1005..xx.xxx) onto a wall, radiation- and precipitationprotected use (for ex. indoor)
		General
		Clamping range
		Ø 20 mm
		Mounting
		plate with with drillings 3 x Ø 6,5 mm
		Material
		plastic, grey flange
		Dimension
		96 mm lang
		Weight
		0.075 kg



Weather and Thermal Radiation Shield, compact
1.1025.55.000

Protective case for the temperature and humidity sensors (2.1280.xx.xxx and 1.1005.54.xxx) sensor compact for outdoor installation without artificial ventilation.

Material

Laminations	plastic, white
Mast holder	stainless stell

General

Mounting	at tube Ø 35 ... 50 mm
Dimension	Ø 120 x 275 mm
Weight	0.8 kg



Weather and Thermal Radiation Shield, compact
1.1025.55.100

Protective case for the preceding temperature sensor compact for outdoor installation with artificial ventilation.

Material

Laminations	plastic, white
Mast holder	stainless stell

General

Power supply	12V DC, 2 W
Electr. connection	5 m cable
Mounting	at tube Ø 35 ... 50 mm
Dimension	Ø 120 x 275 mm
Weight	0.8 kg

